



Castrol Syntrans V FE 75W-80

Fuel Efficient Manual Transmission Fluid - Transaxle

Description

Castrol Syntrans V FE 75W-80 is a full synthetic 75W-80 gear oil designed to provide enhanced EP performance compared with a conventional GL-4 fluid in combination with synchroniser compatibility and fuel efficiency benefits. It is suitable for transaxles, manual gearboxes, transfer boxes and final drives where an API GL-4 lubricant is specified. Recommended by Castrol for all 5- and 6-speed manual transmissions of Volkswagen, Audi, Seat and Skoda.

Advantages

- Low viscosity combined with excellent anti-wear/EP protection ensures the potential for fuel economy benefits in more severe transaxle applications.
- Extremely good cold flow properties provides added protection on start up and improves shift quality.
- Excellent frictional characteristics extends synchroniser life and improves shift comfort.
- High shear stability maintains performance over the lifetime of the lubricant.
- Excellent high temperature stability maintains transmission cleanliness prolonging the life of transmission and lubricant.

| Name | Method | Units | Syntrans V FE 75W-80 |
|------------------------------------|------------------|------------|----------------------|
| Density @ 15C | DIN EN ISO 12185 | g/ml | 0.860 |
| Viscosity, Kinematic 40C | ASTM D445 | mm²/s | 40 |
| Viscosity, Kinematic 100C | ASTM D445 | mm²/s | 8.1 |
| Viscosity Index | DIN ISO 2909 | None | 151 |
| Viscosity, Brookfield @ -40C (75W) | DIN 51398 | mPa.s (cP) | 14000 |
| Pour Point | ISO 3016 | °C | - 60 |
| Flash Point, COC | DIN-ISO 2592 | °C | 220 |
| | | | |

Typical Characteristics

Product Performance Claims

API GL-4+ Audi TL 52532

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Syntrans V FE 75W-80 30 Apr 2015 Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com