



A brand of **TOTAL**

EVOLUTION 900 DID 5W-30



Very high performance lubricant from ELF Synthetic Technology for Gasoline and Diesel car engines, and in particular for Volkswagen TDI direct injection Diesel engines fitted with pump-injector.



APPLICATIONS

Gasoline and Diesel engines

- Recommended for Gasoline and Diesel engines of passenger cars and light commercial vehicles.

New VW direct injection Diesel engines fitted with pump-injector

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications

ACEA : C3
API : SM/CF

OEMs approvals

VOLKSVAGEN VW 502.00/505.01

CUSTOMER BENEFITS

Reduced wear

- Easy starting in all weathers.
- Reduced friction particularly during cold starts, ensuring better lubrication of the engine components.
- Better detergency.

Enhanced thermal stability

- Enhanced thermal stability preventing any degradation even in very severe conditions.
- Excellent protection of the engine particularly against wear at the distribution level.
- Special suitability for VW direct-injection Diesel engines fitted with pump-injectors.

CHARACTERISTICS

	Method	Units	SAE Grade 5W-30
Viscosity at 40°C	ASTM D445	mm ² /s	69
Viscosity at 100°C	ASTM 445	mm ² /s	12
Viscosity index	ASTM D2270	-	171
Pour point	ASTM D97	°C	- 36
Flash point	ASTM D92	°C	230

The typical characteristics mentioned represent mean values